

PAT-NO:

JP406145049A

DOCUMENT-IDENTIFIER: JP 06145049 A

TITLE:

CROSS-LINKING TYPE CATAPLASM BASE

PUBN-DATE:

May 24, 1994

INVENTOR-INFORMATION:

NAME

COUNTRY

YAMAZAKI, KAZUO NAKAMURA, SUSUMU NARA, MASATO NEMOTO, MASAMI

ASSIGNEE-INFORMATION:

NAME

COUNTRY

TAISHO PHARMACEUT CO LTD N/A

APPL-NO: JP04294349

APPL-DATE: November 2, 1992

INT-CL (IPC): A61K009/70 , A61K009/70

ABSTRACT:

PURPOSE: To obtain a cross-linking type cataplasm base having high tack and high base strength in a high cross-linked state free from transfer of plaster to skin during peeling cataplasm.

CONSTITUTION: A cross-linking type cataplasm base consisting essentially of a polyacrylic acid and/or its salt is blended with ≤8wt.%, preferably 0.5-4wt.% silicic acid anhydride having preferably ≤50mµ average particle diameter. The amount of the polyacrylic acid and/or its salt used in the base is 3-20wt.%. Aluminum hydroxide, magnesium metasilicate aluminate, aluminum magnesium hydroxide, synthetic hydrotalcite, etc., as a polyvalent metal salt is used as the cross-linking agent. Optionally a pH adjustor, a stabilizer, an antioxidant, a water-soluble polymer, a water retaining agent, etc.,

10/26/2006, EAST Version: 2.0.3.0



are further added to the cross-linking type cataplasm base. The cross-linking type cataplasm base has excellent balance of tack and strength of base and use of a tacky tape comprising an oily tacky agent or a fixing net which has been utilized in applying a cataplasm having weak tack to the affected part is not required.

COPYRIGHT: (C) 1994, JPO&Japio